



## Product Specifications: **Eastcoast Plush 40mm**

|                                         |                                                                                                                   |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| <b>Type</b>                             | Tufted synthetic grass carpet                                                                                     |
| <b>Yarn material</b>                    | PE Monofilament +PP Curled Yarn                                                                                   |
| <b>Yarn type</b>                        | 11000 / 12F Dtex PE+3500 / 8F Dtex PP                                                                             |
| <b>Yarn thickness</b>                   | 158 micron                                                                                                        |
| <b>Yarn quality</b>                     | Environmentally friendly, UV-stabilised, free of lead and cadmium                                                 |
| <b>Primary backing</b>                  | 100% Double PP black, UV-stabilised. Weight: 220 grams/m <sup>2</sup>                                             |
| <b>Secondary backing</b>                | Black Latex compound with a base of styrenebutadiene (SBR), with drainage holes. Weight: 970 grams/m <sup>2</sup> |
| <b>Tuft gauge</b>                       | 3/8"                                                                                                              |
| <b>Pile height</b>                      | 40 mm (+4%)                                                                                                       |
| <b>Stitches per 10 cm</b>               | 16 (+4%)                                                                                                          |
| <b>Total stitches per m<sup>2</sup></b> | 16,800                                                                                                            |
| <b>Filaments per m<sup>2</sup></b>      | 672,000                                                                                                           |
| <b>Face weight</b>                      | 2,100 grams/m <sup>2</sup> (+4%)                                                                                  |
| <b>Total weight</b>                     | 3,290 grams/m <sup>2</sup> (+4%)                                                                                  |
| <b>Colour</b>                           | Emerald +Olive Green                                                                                              |
| <b>UV-stability</b>                     | Meets EN ISO 4892-3:2006 Standard                                                                                 |
| <b>Colour fastness</b>                  | EN ISO 20105-A02 test: Greyscale > 4                                                                              |
| <b>Water permeability</b>               | 60 litre / min                                                                                                    |
| <b>Infill recommendation</b>            | infill (optional 10 kg/m <sup>2</sup> )                                                                           |